

TOWN OF FREEPORT
CHAPTER 16
FLOODPLAIN MANAGEMENT ORDINANCE

CONTENTS

<u>ARTICLE</u>	<u>PAGE</u>
I. PURPOSE AND ESTABLISHMENT	2
II. PERMIT REQUIRED.....	2
III. APPLICATION FOR PERMIT	2
IV. APPLICATION FEE AND EXPERT'S FEE	4
V. REVIEW STANDARDS FOR FLOOD HAZARD DEVELOPMENT PERMIT APPLICATIONS	5
VI. DEVELOPMENT STANDARDS	6
VII. CONDITIONAL USE REVIEW.....	14
VIII. CERTIFICATE OF COMPLIANCE	15
IX. REVIEW OF SUBDIVISIONS AND DEVELOPMENT PROPOSALS	16
X. APPEALS AND VARIANCES	16
XI. ENFORCEMENT AND PENALTIES	19
XII. VALIDITY AND SEVERABILITY	19
XIII. CONFLICT WITH OTHER ORDINANCES	19
XIV. DEFINITIONS.....	20
XV. ABROGATION	26
XVI. DISCLAIMER OF LIABILITY	26
XVII. DATE OF APPLICABILITY	26

ARTICLE I - PURPOSE AND ESTABLISHMENT

Certain areas of the Town of Freeport, Maine (the “Town”) are subject to periodic flooding, causing serious damages to properties within these areas. Relief is available in the form of flood insurance as authorized by the National Flood Insurance Act of 1968.

Therefore, the Town has chosen to become a participating community in the National Flood Insurance Program and agrees to comply with the requirements of the National Flood Insurance Act of 1968 (P.L. 90-488, as amended) as delineated in this Floodplain Management Ordinance, codified as Chapter 16 of the Freeport Town Ordinances and Codes (the “Ordinance”).

It is the intent of the Town to require the recognition and evaluation of flood hazards in all official actions relating to land use in the floodplain areas having special flood hazards.

The Town has the legal authority to adopt land use and control measures to reduce future flood losses pursuant to, *inter alia*, 30-A M.R.S.A. §§ 3001-3007, 4352, 4401-4407, and 38 M.R.S.A. § 440.

The National Flood Insurance Program, established in the aforesaid Act, provides that areas of the Town of Freeport having a special flood hazard be identified by the Federal Emergency Management Agency and that floodplain management measures be applied in such flood hazard areas. This Ordinance establishes a Flood Hazard Development Permit system and review procedure for development activities in the designated flood hazard areas of the Town.

The areas of special flood hazard, Zones A, AE, and VE for the Town of Freeport, Cumberland County, Maine, identified by the Federal Emergency Management Agency in a report entitled “Flood Insurance Study – Cumberland County, Maine” dated June 20, 2024, with accompanying “Flood Insurance Rate Map” dated June 20, 2024, as amended, are hereby adopted by reference and declared to be a part of this Ordinance.

ARTICLE II - PERMIT REQUIRED

The Codes Enforcement Officer shall be designated as the local Floodplain Administrator. The Floodplain Administrator shall have the authority to implement the commitment made to administer and enforce the requirements for participation in the National Flood Insurance Program.

Before any construction or other development (as defined in Article XIV), including the placement of manufactured homes, begins within any areas of special flood hazard established in Article I, a Flood Hazard Development Permit shall be obtained from the Codes Enforcement Officer, except as provided in Article VII. This permit shall be in addition to any other permits which may be required pursuant to the codes and ordinances of the Town.

ARTICLE III - APPLICATION FOR PERMIT

The application for a Flood Hazard Development Permit shall be submitted to the Codes Enforcement Officer and shall include:

- A. The name, address, and phone number of the applicant, owner, and contractor;
- B. An address and a map indicating the location of the construction site;
- C. A site plan showing locations of existing and/or proposed development, including but not limited to structures, sewage disposal facilities, water supply facilities, areas to be cut and filled, and lot dimensions;
- D. A statement of the intended use of the structure and/or development;
- E. A statement of the cost of the development including all materials and labor;
- F. A statement as to the type of sewage system proposed;
- G. Specification of dimensions of the proposed structure and/or development;

[Items H-K.3. apply only to new construction and substantial improvements.]

H. The elevation in relation to the National Geodetic Vertical Datum (NGVD), North American Vertical Datum (NAVD), or to a locally established datum in Zone A only, of the:

- 1. base flood at the proposed site of all new or substantially improved structures, which is determined:
 - a. in Zones AE, and VE from data contained in the "Flood Insurance Study - Cumberland County, Maine," as described in Article I; or,
 - b. in Zone A:
 - (1) from any base flood elevation data from federal, state, or other technical sources (such as FEMA's Quick-2 model, FEMA 265), including information obtained pursuant to Article VI.M. and IX.D.; or,
 - (2) in the absence of all data described in Article III.H.1.b.(1), information to demonstrate that the structure shall meet the elevation requirement in Article VI.H.2.b., Article VI.I.2.b., or Article VI.J.2.b.
- 2. highest and lowest grades at the site adjacent to the walls of the proposed building;
- 3. lowest floor, including basement; and whether or not such structures contain a basement;
- 4. lowest machinery and equipment servicing the building; and,
- 5. level, in the case of non-residential structures only, to which the structure will be floodproofed.

I. A description of an elevation reference point established on the site of all developments for which elevation standards apply as required in Article VI;

J. A written certification by:

1. a Licensed Professional Land Surveyor that the grade elevations shown on the application are accurate; and,
2. a Licensed Professional Land Surveyor, Professional Engineer or Architect that the base flood elevation shown on the application is accurate.

K. The following certifications as required in Article VI by a Licensed Professional Engineer or architect:

1. a Floodproofing Certificate (FEMA Form FF-206-FY-22-153, as amended), to verify that the floodproofing methods for any non-residential structures will meet the floodproofing criteria of Article VI.I., and other applicable standards in Article VI;
2. a V-Zone Certificate to verify that the construction in coastal high hazard areas, Zone VE and Coastal AE Zone, will meet the criteria of Article VI.R.; and other applicable standards in Article VI;
3. a Hydraulic Openings Certificate to verify that engineered hydraulic openings in foundation walls will meet the standards of Article VI.N.2.a.;
4. a certified statement that bridges will meet the standards of Article VI.O.;
5. a certified statement that containment walls will meet the standards of Article VI.P.

L. A description of the extent to which any water course will be altered or relocated as a result of the proposed development; and,

M. A statement of construction plans describing in detail how each applicable development standard in Article VI will be met.

ARTICLE IV - APPLICATION FEE AND EXPERT'S FEE

Upon application for a permit under this Ordinance, the applicant shall pay a permit fee in accordance with the fee schedule established by the Town Council, as such may be amended by the Town Council from time to time.

An additional fee may be charged if the Codes Enforcement Officer, Project Review Board, and/or Board of Appeals need the assistance of a Licensed Professional Engineer or other expert. The expert's fee shall be paid in full by the applicant within ten (10) days after the Town submits a bill to the applicant. Failure to pay the bill shall constitute a violation of this Ordinance and be grounds for the issuance of a stop work order. An expert shall not be hired by the Town at the expense of an applicant until the applicant has either consented to such hiring in writing or been given an opportunity to be heard on the subject.

ARTICLE V - REVIEW STANDARDS FOR FLOOD HAZARD DEVELOPMENT PERMIT APPLICATIONS

The Codes Enforcement Officer shall:

- A. Review all applications for the Flood Hazard Development Permit to assure that proposed developments are reasonably safe from flooding and to determine that all pertinent requirements of Article VI (Development Standards) have been, or will be met;
- B. Utilize, in the review of all Flood Hazard Development Permit applications:
 - 1. the base flood and floodway data contained in the "Flood Insurance Study - Cumberland County, Maine," as described in Article I;
 - 2. in special flood hazard areas where base flood elevation and floodway data are not provided, the Codes Enforcement Officer shall obtain, review, and reasonably utilize any base flood elevation and floodway data from federal, state, or other technical sources, including information obtained pursuant to Article III.H.1.b.(1); Article VI.M.; and Article IX.D., in order to administer Article VI of this Ordinance; and,
 - 3. when the community establishes a base flood elevation in a Zone A by methods outlined in Article III.H.1.b.(1), the community shall submit that data to the Maine Floodplain Management Program.
- C. Make interpretations of the location of boundaries of special flood hazard areas shown on the maps described in Article I of this Ordinance;
- D. In the review of Flood Hazard Development Permit applications, determine that all necessary permits have been obtained from those federal, state, and local government agencies from which prior approval is required by federal or state law, including but not limited to Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1344;
- E. Notify adjacent municipalities, the Department of Environmental Protection, and the Maine Floodplain Management Program prior to any alteration or relocation of a water course and submit copies of such notifications to the Federal Emergency Management Agency;
- F. If the application satisfies the requirements of this Ordinance, approve the issuance of one (1) of the following Flood Hazard Development Permits, based on the type of development:
 - 1. A two-part Flood Hazard Development Permit for elevated structures. Part I shall authorize the applicant to build a structure to and including the first horizontal floor only above the base flood level. At that time the applicant shall provide the Codes Enforcement Officer with an "under construction" Elevation Certificate completed by a Licensed Professional Land Surveyor based on the Part I permit construction for verifying compliance with the elevation requirements of Article VI, paragraphs H., I., J., or R. Following review of the Elevation Certificate data, which

shall take place within thirty (30) days of receipt of the application, the Codes Enforcement Officer shall issue Part II of the Flood Hazard Development Permit. Part II shall authorize the applicant to complete the construction project; or,

2. A Flood Hazard Development Permit for Floodproofing of Non-Residential Structures that are new construction or substantially improved non-residential structures that are not being elevated but that meet the floodproofing standards of Article VI.I.1. The application for this permit shall include a Floodproofing Certificate signed by a Licensed Professional Engineer or Architect; or,
3. A Flood Hazard Development Permit for Minor Development for all development that is not new construction or a substantial improvement, such as repairs, maintenance, renovations, or additions, whose value is less than fifty (50%) percent of the market value of the structure. Minor development also includes but is not limited to: accessory structures as provided for in Article VI.L., mining, dredging, filling, grading, paving, excavation, drilling operations, storage of equipment or materials, deposition or extraction of materials, public or private sewage disposal systems or water supply facilities that do not involve structures; and non-structural projects such as bridges, dams, towers, fencing, pipelines, wharves, and piers.

For development that requires review and approval as a Conditional Use, as provided for in this Ordinance, the Flood Hazard Development Permit Application shall be acted upon by the Project Review Board as required in Article VII.

- G. Maintain, as a permanent record, copies of all Flood Hazard Development Permit Applications, corresponding Permits issued, and data relevant thereto, including reports of the Board of Appeals on variances granted under the provisions of Article X of this Ordinance, and copies of Elevation Certificates, Floodproofing Certificates, Certificates of Compliance, and certifications of design standards required under the provisions of Articles III, VI, and VIII of this Ordinance.

ARTICLE VI - DEVELOPMENT STANDARDS

All developments in areas of special flood hazard shall meet the following applicable standards:

A. All Development - All development shall:

1. be designed or modified and adequately anchored to prevent flotation (excluding piers and docks), collapse, or lateral movement of the development resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy;
2. use construction materials that are resistant to flood damage;
3. use construction methods and practices that will minimize flood damage; and,
4. use electrical, heating, ventilation, plumbing, and air conditioning equipment, and other service facilities that are designed and/or located to prevent water from entering or accumulating within the components during flooding conditions.

- B. Water Supply** - All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the systems.
- C. Sanitary Sewage Systems** - All new and replacement sanitary sewage systems shall be designed and located to minimize or eliminate infiltration of flood waters into the system and discharges from the system into flood waters.
- D. On Site Waste Disposal Systems** - On site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during floods.
- E. Watercourse Carrying Capacity** - All development associated with altered or relocated portions of a watercourse shall be constructed and maintained in such a manner that no reduction occurs in the flood carrying capacity of the watercourse.
- F. Utilities** - New construction or substantial improvement of any structure (including manufactured homes) located within:
1. Zones A and AE shall have the bottom of all electrical, heating, plumbing, ventilation and air conditioning equipment, permanent fixtures and components, HVAC ductwork and duct systems, and any other utility service equipment, facilities, machinery, or connections servicing a structure, elevated to at least one (1) foot above the base flood elevation.
 2. Zone VE shall meet the requirements of Article VI.R.2.
- G. Physical Changes to the Natural Landscape** - Certain development projects, including but not limited to, retaining walls, sea walls, levees, berms, and rip rap, can cause physical changes that affect flooding conditions.
1. All development projects in Zones AE, Coastal AE (as defined) and VE that cause physical changes to the natural landscape shall be reviewed by a qualified professional to determine whether or not the project changes the base flood elevation, zone, and/or the flood hazard boundary line.
 - a. If the qualified professional determines, through the use of standard practices, that the project would not necessitate a Letter of Map Revision (LOMR), a certified statement shall be provided.
 - b. If the qualified professional determines that the project may cause a change, a hydrologic and hydraulic analysis that meets current FEMA standards shall be performed.
 2. If the hydrologic and hydraulic analysis performed indicates a change to the base flood elevation, zone, and/or the flood hazard boundary line, the applicant may submit a Conditional Letter of Map Revision (C-LOMR) request to the Federal Emergency Management Agency for assurance that the as-built project will result in a change to the Flood Insurance Rate Map. Once the development is completed, a request for a Letter of Map Revision (LOMR) shall be initiated; or

3. If the hydrologic and hydraulic analysis performed show a change to the base flood elevation, zone, and/or the flood hazard boundary line, as soon as practicable, but no later than six (6) months after the completion of the project, the applicant shall submit the technical data to FEMA in the form of a Letter of Map Revision request.

H. Residential - New construction or substantial improvement of any residential structure located within:

1. Zones AE shall have the lowest floor (including basement) elevated to at least one (1) foot above the base flood elevation.
2. Zone A shall have the lowest floor (including basement) elevated:
 - a. to at least one (1) foot above the base flood elevation utilizing information obtained pursuant to Article III.H.1.b.(1); Article V.B.; or Article IX.D., or;
 - b. in the absence of all data described in Article VI.H.2.a., to at least two (2) feet above the highest adjacent grade to the structure.
3. Zone VE and Coastal AE Zone (as defined) shall meet the requirements of Article VI.R.

I. Non-Residential - New construction or substantial improvement of any non-residential structure located within:

1. Zones AE shall have the lowest floor (including basement) elevated to at least one (1) foot above the base flood elevation, or together with attendant utility and sanitary facilities shall:
 - a. be floodproofed to at least one (1) foot above the base flood elevation so that below that elevation the structure is watertight with walls substantially impermeable to the passage of water;
 - b. have structural components capable of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy; and,
 - c. be certified by a Licensed Professional Engineer or Architect that the floodproofing design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this section. Such certification shall be provided with the application for a Flood Hazard Development Permit, as required by Article III.K., and shall include a record of the elevation above mean sea level to which the structure is floodproofed.
2. Zone A shall have the lowest floor (including basement) elevated:
 - a. to at least one (1) foot above the base flood elevation utilizing information obtained pursuant to Article III.H.1.b.(1); Article V.B.; or Article IX.D., or;

b. in the absence of all data described in Article VI.I.2.a., to at least two (2) feet above the highest adjacent grade to the structure; or,

c. together with attendant utility and sanitary facilities, be floodproofed to one (1) foot above the elevation established in Article VI.I.2.a. or b. and meet the floodproofing standards of Article VI.I.1.a., b., and c.

3. Zone VE and Coastal AE Zone (as defined) shall meet the requirements of Article VI.R.

J. Manufactured Homes - New or substantially improved manufactured homes located within:

1. Zones AE shall:

a. be elevated such that the lowest floor (including basement) of the manufactured home is at least one (1) foot above the base flood elevation;

b. be on a permanent foundation, which may be poured masonry slab or foundation walls, with hydraulic openings, or may be reinforced piers or block supports, any of which support the manufactured home so that no weight is supported by its wheels and axles; and,

c. be securely anchored to an adequately anchored foundation system to resist flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to:

(1) over-the-top ties anchored to the ground at the four corners of the manufactured home, plus two (2) additional ties per side at intermediate points (manufactured homes less than fifty (50) feet long require one (1) additional tie per side); or by,

(2) frame ties at each corner of the home, plus five additional ties along each side at intermediate points (manufactured homes less than fifty (50) feet long require four additional ties per side).

(3) All components of the anchoring system described in Article VI.J.1.c.(1) & (2) shall be capable of carrying a force of four thousand eight hundred (4800) pounds.

2. Zone A shall:

a. be elevated on a permanent foundation, as described in Article VI.J.1.b., such that the lowest floor (including basement) of the manufactured home is at least one (1) foot above the base flood elevation utilizing information obtained pursuant to Article III.H.1.b.(1); Article V.B.; or Article IX.D.; or,

b. in the absence of all data described in Article VI.J.2.a., to at least two (2) feet above the highest adjacent grade to the structure; and,

c. meet the anchoring requirements of VI.J.1.c.

3. Zone VE and Coastal AE Zone (as defined) shall meet the requirements of Article VI.R.

K. Recreational Vehicles - Recreational Vehicles located within:

1. Zones A and AE shall either:

- a. be on the site for fewer than one hundred eighty (180) consecutive days; and,
- b. be fully licensed and ready for highway use. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached additions; or,
- c. be permitted in accordance with the elevation and anchoring requirements for "manufactured homes" in Article VI.J.1.

2. Zone VE and Coastal AE Zone (as defined) shall meet the requirements of either Article VI.K.1.a. and b., or Article VI.R.

L. Accessory Structures - New construction or substantial improvement of Accessory Structures, as defined in Article XIV, shall be exempt from the elevation criteria required in Article VI.H. & I. above, if all other requirements of Article VI and all the following requirements are met.

1. Accessory Structures located in Zone A and AE shall:

- a. meet the requirements of Article VI.A.1. through 4., as applicable;
- b. be limited in size to a one (1) story two (2) car garage;
- c. have unfinished interiors and not be used for human habitation;
- d. have only ground fault interrupt electrical outlets. The electric service disconnect shall be located above the base flood elevation and, when possible, outside the Special Flood Hazard Area;
- e. be located outside the floodway;
- f. when possible be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters and be placed further from the source of flooding than is the primary structure;
- g. have hydraulic openings, as specified in Article VI.N.2., in at least two (2) different walls of the accessory structure; and
- h. be located outside the Coastal AE Zone.

2. Accessory Structures in Zone VE and Coastal A Zones shall meet the requirements of Article VI.R.

M. Floodways -

1. In Zone AE riverine areas, encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted within a regulatory floodway which is designated on the community's Flood Insurance Rate Map unless a technical evaluation certified by a Licensed Professional Engineer is provided demonstrating that such encroachments will not result in any increase in flood levels within the community during the occurrence of the base flood discharge.
2. In Zones A and AE riverine areas, for which no regulatory floodway is designated, encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted in the floodway as determined in Article VI.M.3. unless a technical evaluation certified by a Licensed Professional Engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing development and anticipated development:
 - a. will not increase the water surface elevation of the base flood more than one (1) foot at any point within the community; and,
 - b. is consistent with the technical criteria contained in FEMA's guidelines and standards for flood risk analysis and mapping.
3. In Zones A and AE riverine areas, for which no regulatory floodway is designated, the regulatory floodway is determined to be the channel of the river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain as measured from the normal high water mark to the upland limit of the floodplain.

N. Hydraulic Openings/Flood Vents - New construction or substantial improvement of any structure in Zones A and AE that meets the development standards of Article VI, including the elevation requirements of Article VI, paragraphs H., I., or J. and is elevated on posts, columns, piers, piles, or crawl spaces may be enclosed below the base flood elevation requirements provided all the following criteria are met or exceeded:

1. Enclosed areas are not "basements" as defined in Article XIV;
2. Enclosed areas shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of flood water. Designs for meeting this requirement must either:
 - a. be engineered and certified by a Licensed Professional Engineer or Architect; or,
 - b. meet or exceed the following minimum criteria:

(1) a minimum of two (2) openings having a total net area of not less than one (1) square inch for every one (1) square foot of the enclosed area;

(2) the bottom of all openings shall be below the base flood elevation and no higher than one (1) foot above the lowest grade; and,

(3) openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the entry and exit of flood waters automatically without any external influence or control such as human intervention, including the use of electrical and other non-automatic mechanical means;

3. The enclosed area shall not be used for human habitation; and,

4. The enclosed areas are usable solely for building access, parking of vehicles, or storage.

O. **Bridges** - New construction or substantial improvement of any bridge in Zones A, AE, and VE shall be designed such that:

1. when possible, the lowest horizontal member (excluding the pilings or columns) is elevated to at least one (1) foot above the base flood elevation; and,

2. a Licensed Professional Engineer shall certify that:

a. the structural design and methods of construction shall meet the elevation requirements of this section and the floodway standards of Article VI.M.; and,

b. the foundation and superstructure attached thereto are designed to resist flotation, collapse, and lateral movement due to the effects of wind and water loads acting simultaneously on all structural components. Water loading values used shall be those associated with the base flood.

P. **Containment Walls** - New construction or substantial improvement of any containment wall located within:

1. Zones A, AE, and VE shall:

a. have the containment wall elevated to at least one (1) foot above the base flood elevation;

b. have structural components capable of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy; and,

c. be certified by a Licensed Professional Engineer or Architect that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this section. Such certification shall be provided with the application for a Flood Hazard Development Permit, as required by Article III.K.

Q. Wharves, Piers, and Docks - New construction or substantial improvement of wharves, piers, and docks are permitted in and over water and seaward of the mean high tide if the following requirements are met:

1. in Zones AE, Coastal AE (as defined) and VE, wharves, piers, and docks shall comply with all applicable local, state, and federal regulations; must be reasonably safe from flooding; and must not increase flood risk; and,
2. in Zone VE, permanent wharves, piers, and docks shall have a Qualified Professional develop or review the structural design and specifications; must be reasonably safe from flooding; and must not increase flood risk.

R. Coastal Floodplains -

1. New construction located within Zones AE and VE shall be located landward of the reach of mean high tide except as provided in Article VI.R.7.
2. New construction or substantial improvement of any structure located within Zone VE or Coastal AE Zone shall have the bottom of all electrical, heating, plumbing, ventilation and air conditioning equipment, permanent fixtures and components, HVAC ductwork and duct systems, and any other utility service equipment, facilities, machinery, or connections servicing a structure, elevated to at least one (1) foot above the base flood elevation. Systems, fixtures, equipment, and components shall not be mounted on or penetrate through walls intended to break away under flood loads.
3. New construction or substantial improvement of any structure located within Zone VE and Coastal AE Zones (as defined) shall:

a. be elevated on posts or columns such that:

- (1) the bottom of the lowest horizontal structural member of the lowest floor (excluding the pilings or columns) is elevated to at least one (1) foot above the base flood elevation;
- (2) the pile or column foundation and the elevated portion of the structure attached thereto is anchored to resist flotation, collapse, and lateral movement due to the effects of wind and water loads acting simultaneously on all building components; and,
- (3) water loading values used shall be those associated with the base flood. Wind loading values used shall be those required by applicable state and local building standards.

b. have the space below the lowest floor:

- (1) free of obstructions; or,

(2) constructed with open wood lattice-work, or insect screening intended to collapse under wind and water without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting piles or columns; or,

(3) constructed with non-supporting breakaway walls that have a design safe loading resistance of not less than ten (10) or more than twenty (20) pounds per square foot.

c. require a Licensed Professional Engineer or architect to:

(1) develop or review the structural design, specifications, and plans for the construction, which must meet or exceed the technical criteria contained in the *Coastal Construction Manual*, (FEMA-55); and,

(2) certify that the design and methods of construction to be used are in accordance with accepted standards of practice for meeting the criteria of Article VI.R.3.

4. The use of fill for structural support in Zone VE and Coastal AE Zones is prohibited.

5. Human alteration of sand dunes within Zone VE and Coastal AE Zones is prohibited unless it can be demonstrated that such alterations will not increase potential flood damage.

6. The area below the lowest floor shall be used solely for parking vehicles, building access, and storage.

7. Physical changes to the natural landscape in Zone VE are subject to the requirements in Article VI.G.

8. Wharves, piers, and docks in Zone VE are subject to the requirements in Article VI.Q.

9. Conditional Use - Lobster sheds and fishing sheds may be located seaward of mean high tide and shall be exempt from the elevation requirement in Article VI.I. only if permitted as a Conditional Use following review and approval by the Project Review Board, as provided in Article VII, and if all the following requirements and those of Article VI.A., VI.M., and VI.N. are met:

a. The conditional use shall be limited to low value structures such as metal or wood sheds two hundred (200) square feet or less and shall not exceed more than one (1) story.

b. The structure shall be securely anchored to the wharf or pier to resist flotation, collapse, and lateral movement due to the effect of wind and water loads acting simultaneously on all building components.

c. The structure will not adversely increase wave or debris impact forces affecting nearby buildings.

d. The structure shall have unfinished interiors and shall not be used for human habitation.

- e. Any mechanical, utility equipment, and fuel storage tanks must be anchored and either elevated or floodproofed to at least one (1) foot above the base flood elevation.
- f. All electrical outlets shall be ground fault interrupt type. The electrical service disconnect shall be located on shore above the base flood elevation and, when possible, outside the Special Flood Hazard Area.

ARTICLE VII - CONDITIONAL USE REVIEW

The Project Review Board shall hear and decide upon applications for conditional uses provided for in this Ordinance. The Project Review Board shall hear and approve, approve with conditions, or disapprove all applications for conditional uses. An applicant informed by the Codes Enforcement Officer that a Conditional Use Permit is required shall file an application for the permit with the Project Review Board.

A. Review Procedure for a Conditional Use Flood Hazard Development Permit

- 1. The Flood Hazard Development Permit Application with additional information attached addressing how each of the conditional use criteria specified in this Ordinance will be satisfied may serve as the permit application for the Conditional Use Permit.
- 2. Before deciding any application, the Project Review Board shall hold a public hearing on the application within thirty days of their receipt of the application.
- 3. If the Project Review Board finds that the application satisfies all relevant requirements of this Ordinance, the Project Review Board must approve the application or approve with conditions within forty-five (45) days of the date of the public hearing.
- 4. A Conditional Use Permit issued under the provisions of this Ordinance shall expire if the work or change involved is not commenced within one hundred (180) days of the issuance of the permit by the Project Review Board.
- 5. The applicant shall be notified by the Project Review Board in writing over the signature of the Chairperson of the Project Review Board that flood insurance is not available for structures located entirely over water or seaward of mean high tide.

B. Expansion of Conditional Uses

- 1. No existing building or use of premises may be expanded or enlarged without a permit issued under this section if that building or use was established or constructed under a previously issued Conditional Use Permit or if it is a building or use which would require a Conditional Use Permit if being newly-established or constructed under this Ordinance.

ARTICLE VIII - CERTIFICATE OF COMPLIANCE

No land in a special flood hazard area shall be occupied or used and no structure which is constructed or substantially improved shall be occupied until a Certificate of Compliance is issued by the Codes Enforcement Officer subject to the following provisions:

A. For New Construction or Substantial Improvement of any elevated structure the applicant shall submit to the Codes Enforcement Officer:

1. an Elevation Certificate completed by a Professional Land Surveyor for compliance with Article VI, paragraphs H., I., J., or R.; and,
2. for structures in Zone VE and Coastal AE Zone (as defined), certification by a Licensed Professional Engineer or Architect that the design and methods of construction used are in compliance with Article VI.R.3.

B. The applicant shall submit written notification to the Codes Enforcement Officer that the development is complete and complies with the provisions of this Ordinance.

C. Within ten (10) working days, the Codes Enforcement Officer shall:

1. review the required certificate(s) and the applicant's written notification; and,
2. upon determination that the development conforms to the provisions of this Ordinance, shall issue a Certificate of Compliance.

ARTICLE IX - REVIEW OF SUBDIVISION AND DEVELOPMENT PROPOSALS

The Project Review Board shall, when reviewing subdivisions and other proposed developments that require review under other federal law, state law, local ordinances or regulations, and all projects on five (5) or more disturbed acres, or in the case of manufactured home parks divided into two (2) or more lots, assure that:

A. All such proposals are consistent with the need to minimize flood damage.

B. All public utilities and facilities, such as sewer, gas, electrical, and water systems are located and constructed to minimize or eliminate flood damages.

C. Adequate drainage is provided so as to reduce exposure to flood hazards.

D. All proposals include base flood elevations, flood boundaries, and, in a riverine floodplain, floodway data. These determinations shall be based on engineering practices recognized by the Federal Emergency Management Agency.

E. Any proposed development plan must include a condition of plan approval requiring that structures on any lot in the development having any portion of its land within a Special Flood Hazard Area are to be constructed in accordance with Article VI of this Ordinance. Such requirement will be included in any deed, lease, purchase and sale agreement, or document transferring or expressing an intent to

transfer any interest in real estate or structure, including but not limited to a time-share interest. The condition shall clearly articulate that the Town may enforce any violation of the construction requirement and that fact shall also be included in the deed or any other document previously described. The construction requirement shall also be clearly stated on any map, plat, or plan to be signed by the Project Review Board or local reviewing authority as part of the approval process.

ARTICLE X - APPEALS AND VARIANCES

Powers and Duties of the Board of Appeals:

The Board of Appeals may, upon written application of an aggrieved party, hear and decide administrative appeals where it is alleged that there is an error in any order, requirement, decision, or determination made by, the Codes Enforcement Officer in the administration or enforcement of the provisions of this Ordinance.

The Board of Appeals shall not have the power to hear or decide administrative appeals of any order, requirement, decision, or determination made by, the Project Review Board. Any such appeal shall be made directly to the Superior Court in accordance with Rule 80B of the Maine Rules of Civil Procedure.

The Board of Appeals may grant a variance from the requirements of this Ordinance consistent with the requirements of Section 601.G.2.b of Chapter 21, Town of Freeport Zoning Ordinance; applicable state law; and the criteria set forth in Article X.A through G, below.

In hearing and deciding any administrative appeal or variance appeal, the Board of Appeals shall follow the administrative provisions set forth in Section 601.G Board of Appeals of Chapter 21, Town of Freeport Zoning Ordinance and 30-A M.R.S.A. § 2691.

Variance Appeals:

A. Variances shall not be granted within any designated regulatory floodway if any increase in flood levels during the base flood discharge would result.

B. Variances shall be granted only upon:

1. a showing of good and sufficient cause; and,

2. a determination that should a flood comparable to the base flood occur, the granting of a variance will not result in increased flood heights, additional threats to public safety, public expense, or create nuisances, cause fraud or victimization of the public, or conflict with existing local laws or ordinances; and,

3. a showing that the issuance of the variance will not conflict with other state, federal, or local laws or ordinances; and,

4. a determination that failure to grant the variance would result in "undue hardship," which in this sub-section means:

- a. that the land in question cannot yield a reasonable return unless a variance is granted; and,
 - b. that the need for a variance is due to the unique circumstances of the property and not to the general conditions in the neighborhood; and,
 - c. that the granting of a variance will not alter the essential character of the locality; and,
 - d. that the hardship is not the result of action taken by the applicant or a prior owner.
- C. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief, and the Board of Appeals may impose such conditions to a variance as is deemed necessary.
- D. Variances may be issued for new construction, substantial improvements, or other development for the conduct of a functionally dependent use provided that:
 - 1. the criteria of Article X.A. through C. and Article VI.M. are met; and,
 - 2. the structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety.
- E. Variances may be issued for the repair, reconstruction, rehabilitation, or restoration of Historic Structures upon the determination that:
 - 1. the development meets the criteria of Article X.A. through C.; and,
 - 2. the proposed repair, reconstruction, rehabilitation, or restoration will not preclude the structure's continued designation as a Historic Structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
- F. Variances may be issued for new construction and substantial improvement of Agricultural Structures being used for the conduct of agricultural uses provided that:
 - 1. the development meets the criteria of Article X.A. through C.; and,
 - 2. the development meets the criteria of Article VI.M. and Article VI.N.
- G. Any applicant who meets the criteria of Article X.A. through C. and Article X.D., E., or F. shall be notified by the Board of Appeals in writing over the signature of the Chairperson of the Board of Appeals that:
 - 1. the issuance of a variance to construct a structure below the base flood level will result in greatly increased premium rates for flood insurance up to amounts as high as twenty-five (25) dollars per one hundred (100) dollars of insurance coverage; and,

2. such construction below the base flood level increases risks to life and property; and,
3. the applicant agrees in writing that the applicant is fully aware of all the risks inherent in the use of land subject to flooding, assumes those risks, and agrees to indemnify and defend the Town against any claims filed against it that are related to the applicant's decision to use land located in a floodplain and that the applicant individually releases the Town from any claims the applicant may have against the Town that are related to the use of land located in a floodplain.

ARTICLE XI - ENFORCEMENT AND PENALTIES

- A. It shall be the duty of the Codes Enforcement Officer to enforce the provisions of this Ordinance pursuant to 30-A M.R.S.A. § 4452.
- B. The penalties contained in 30-A M.R.S.A. § 4452 shall apply to any violation of this Ordinance.
- C. In addition to other actions, the Codes Enforcement Officer, upon identifying a violation, may submit a declaration to the Administrator of the Federal Insurance Administration requesting a flood insurance denial. The valid declaration shall consist of:
 1. the name of the property owner and address or legal description of the property sufficient to confirm its identity or location;
 2. a clear and unequivocal declaration that the property is in violation of a cited State or local law, regulation, or ordinance;
 3. a clear statement that the public body making the declaration has authority to do so and a citation to that authority;
 4. evidence that the property owner has been provided notice of the violation and the prospective denial of insurance; and,
 5. a clear statement that the declaration is being submitted pursuant to Section 1316 of the National Flood Insurance Act of 1968, as amended.

ARTICLE XII - VALIDITY AND SEVERABILITY

If any section or provision of this Ordinance is declared by the courts to be invalid, such decision shall not invalidate any other section or provision of this Ordinance.

ARTICLE XIII - CONFLICT WITH OTHER ORDINANCES

This Ordinance shall not in any way impair or remove the necessity of compliance with any other applicable rule, ordinance, regulation, bylaw, permit, or provision of law. Where this Ordinance imposes a greater restriction upon the use of land, buildings, or structures, the provisions of this Ordinance shall control.

ARTICLE XIV - DEFINITIONS

Unless specifically defined below, words and phrases used in this Ordinance shall have the same meaning as they have at common law, and to give this Ordinance its most reasonable application. Words used in the present tense include the future, the singular number includes the plural, and the plural number includes the singular. The word "may" is permissive; "shall" and "must" is mandatory and not discretionary.

Accessory Structure - a structure which is on the same parcel of property as a principal structure and the use of which is incidental to the use of the principal structure.

Adjacent Grade - the natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

Agricultural Structure - structures that are used exclusively for agricultural purposes or uses in connection with the production, harvesting, storage, raising, or drying of agricultural commodities and livestock. Structures that house tools or equipment used in connection with these purposes or uses are also considered to have agricultural purposes or uses.

Area of Special Flood Hazard - land in the floodplain having a one (1) percent or greater chance of flooding in any given year, as specifically identified in the Flood Insurance Study cited in Article I of this Ordinance.

Base Flood - a flood having a one (1) percent chance of being equaled or exceeded in any given year, commonly called the one hundred (100) year flood.

Basement - any area of a building that includes a floor that is subgrade (below ground level) on all sides.

Breakaway Wall - a wall that is not part of the structural support of the building and is intended through its design and construction to collapse under specific lateral loading forces, without causing damage to the elevated portion of the building or supporting foundation system.

Building - see **Structure**.

Certificate of Compliance - a document signed by the Codes Enforcement Officer stating that a structure is in compliance with all of the provisions of this Ordinance.

Coastal AE Zone - The portion of the Coastal High Hazard Area with wave heights between one point five (1.5) feet and three (3.0) feet and bounded by a line labeled the "Limit of Moderate Wave Action" (LiMWA) on a Flood Insurance Rate Map (FIRM). VE Zone floodplain construction standards are applied to development, new construction, and substantial improvements in the Coastal AE Zone.

Coastal High Hazard Area - An area of special flood hazard extending from offshore to the inland limit of a primary frontal dune along an open coast and any other area subject to high velocity wave action from storms or seismic sources. Coastal High Hazard Areas are designated as Zone VE and Zone AE bounded by a line labeled "Limit of Moderate Wave Action" (LiMWA) on a Flood Insurance Rate Map (FIRM).

Codes Enforcement Officer - a person certified under 30-A M.R.S.A. § 4451 (including exceptions in 30-A M.R.S.A. § 4451(1)) and employed by The Town to enforce all applicable comprehensive planning and land use laws.

Conditional Use - a use that, because of its potential impact on surrounding areas and structures, is permitted only upon review and approval by the Project Review Board pursuant to Article VII.

Containment Wall - a wall surrounding all sides of an above ground tank to contain any spills or leaks.

Development - any manmade change to improved or unimproved real estate. This includes, but is not limited to, buildings or other structures; mining, dredging, filling, grading, paving, excavation, drilling operations or storage of equipment or materials; and the storage, deposition, or extraction of materials.

Elevated Building - a non-basement building that is:

- a. built, in the case of a building in Zones A or AE, so that the top of the elevated floor, or in the case of a building in Zone VE or Coastal AE Zone, to have the bottom of the lowest horizontal structural member of the elevated floor, elevated above the ground level by means of pilings, columns, posts, or piers; and,
- b. adequately anchored to not impair the structural integrity of the building during a flood of up to one (1) foot above the magnitude of the base flood.

In the case of Zones A or AE, **Elevated Building** also includes a building elevated by means of fill or solid foundation perimeter walls with hydraulic openings sufficient to facilitate the unimpeded movement of flood waters, as required in Article VI.N. In the case of Zone VE and Coastal AE Zone, **Elevated Building** also includes a building otherwise meeting the definition of elevated building, even though the lower area is enclosed by means of breakaway walls, if the breakaway walls meet the standards of Article VI.R.3.b.(3).

Elevation Certificate - an official form (FEMA Form FF-206-FY-22-152, as amended) that is used to verify compliance with the floodplain management regulations of the National Flood Insurance Program.

Existing Manufactured Home Park or Subdivision - a manufactured home park or subdivision that was recorded in the deed registry prior to the adoption date of the community's first floodplain management regulations.

Flood or Flooding -

- a. A general and temporary condition of partial or complete inundation of normally dry land areas from:
 1. The overflow of inland or tidal waters.
 2. The unusual and rapid accumulation or runoff of surface waters from any source.

b. The collapse or subsidence of land along the shore of a body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph a.1. of this definition.

Flood Elevation Study - an examination, evaluation, and determination of flood hazards and, if appropriate, corresponding water surface elevations.

Flood Insurance Rate Map (FIRM) - an official map of a community, on which the Federal Insurance Administrator has delineated both the special hazard areas and the risk premium zones applicable to the community.

Flood Insurance Study - see **Flood Elevation Study**.

Floodplain or Floodprone Area - any land area susceptible to being inundated by water from any source (see **Flood or Flooding**).

Floodplain Management - the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works, and floodplain management regulations.

Floodplain Management Regulations - zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a floodplain ordinance, grading ordinance, and erosion control ordinance), and other applications of police power. The term describes such state or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.

Floodproofing - any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures, and contents.

Floodway - see **Regulatory Floodway**.

Floodway Encroachment Lines - the lines marking the limits of floodways on federal, state, and local floodplain maps.

Freeboard - a factor of safety usually expressed in feet above a flood level for purposes of floodplain management. Freeboard tends to compensate for the many unknown factors, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed, which could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions.

Functionally Dependent Use - a use which cannot perform its intended purpose unless it is located or carried out in close proximity to water. The term includes only docking facilities, port facilities that are

necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

Historic Structure - any structure that is:

- a. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- b. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary of the Interior to qualify as a registered historic district;
- c. Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or,
- d. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
 1. By an approved state program as determined by the Secretary of the Interior, or,
 2. Directly by the Secretary of the Interior in states without approved programs.

Limit of Moderate Wave Action (LiMWA) - The landward limit of the one point five (1.5) foot breaking wave within a Coastal AE Zone. These areas are bounded by a line labeled “Limit of Moderate Wave Action” (LiMWA) on a Flood Insurance Rate Map (FIRM). The LiMWA line delineates that portion of the Special Flood Hazard Area (SFHA) landward of a VE zone in which the principal sources of flooding are astronomical high tides, storm surges, or tsunamis, not riverine sources. These areas may be subject to wave effects, velocity flows, erosion, scour, or combinations of these forces. The floodplain development and construction standards for VE Zones will be applied in the Coastal AE Zone.

Locally Established Datum - for purposes of this Ordinance, an elevation established for a specific site to which all other elevations at the site are referenced. This elevation is generally not referenced to the National Geodetic Vertical Datum (NGVD), North American Vertical Datum (NAVD), or any other established datum and is used in areas where Mean Sea Level data is too far from a specific site to be practically used.

Lowest Floor - the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access, or storage in an area other than a basement area is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements described in Article VI.N. of this Ordinance.

Manufactured Home - a structure, transportable in one (1) or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For floodplain management purposes the term manufactured home also includes park

trailers, travel trailers, and other similar vehicles placed on a site for greater than one hundred (180) consecutive days.

Manufactured Home Park or Subdivision - a parcel (or contiguous parcels) of land divided into two (2) or more manufactured home lots for rent or sale.

Mean Sea Level - for the purposes of the National Flood Insurance Program, the National Geodetic Vertical Datum (NGVD) of 1929, North American Vertical Datum (NAVD), or other datum, to which base flood elevations shown on a community's Flood Insurance Rate Map are referenced.

Minor Development - all development that is not new construction or a substantial improvement, such as repairs, maintenance, renovations, or additions, whose value is less than 50% of the market value of the structure. It also includes but is not limited to: accessory structures as provided for in Article VI.L., mining, dredging, filling, grading, paving, excavation, drilling operations, storage of equipment or materials, deposition or extraction of materials, public or private sewage disposal systems or water supply facilities that do not involve structures; and non-structural projects such as bridges, dams, towers, fencing, pipelines, wharves, and piers.

National Geodetic Vertical Datum (NGVD) - the national vertical datum, a standard established in 1929, which is used by the National Flood Insurance Program (NFIP). NGVD is based upon mean sea level in 1929 and has been called "1929 Mean Sea Level" (MSL).

New Construction - structures for which the "start of construction" commenced on or after the effective date of the initial floodplain management regulations adopted by a community and includes any subsequent improvements to such structures.

North American Vertical Datum (NAVD) - the national datum whose standard was established in 1988, which is the new vertical datum used by the National Flood Insurance Program (NFIP) for all new Flood Insurance Rate Maps. NAVD is based upon the vertical data used by other North American countries such as Canada and Mexico and was established to replace NGVD because of constant movement of the earth's crust, glacial rebound and subsidence, and the increasing use of satellite technology.

One Hundred (100) year flood - see **Base Flood**.

Qualified Professional: means an individual either licensed by the State of Maine or qualified in another manner to perform the specified work and in accordance with all applicable design standards and codes, and whose qualifications indicate that the work as designed and as performed will not increase flood risk to public safety. If the Qualified Professional is not licensed by the State of Maine, the local permitting authority should identify the qualifications of the professional in writing.

Recreational Vehicle - a vehicle that is:

- a. built on a single chassis;
- b. four hundred (400) square feet or less when measured at the largest horizontal projection, not including slideouts;

- c. designed to be self-propelled or permanently towable by a motor vehicle; and,
- d. designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

Regulatory Floodway -

- a. the channel of a river or other water course and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height, and,
- b. when not designated on the community's Flood Insurance Rate Map, it is considered to be the channel of a river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain, as measured from the normal high-water mark to the upland limit of the floodplain.

Riverine - relating to, formed by, or resembling a river (including tributaries), stream, brook, etc.

Special Flood Hazard Area - see Area of Special Flood Hazard.

Start of Construction - the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, substantial improvement, or other improvement was within one hundred (180) days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, or modification of any construction element, whether or not that alteration affects the external dimensions of the building.

Structure - for floodplain management purposes, a walled and roofed building. A gas or liquid storage tank that is principally above ground is also a structure.

Substantial Damage - damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damage condition would equal or exceed fifty (50%) percent of the market value of the structure before the damage occurred.

Substantial Improvement - any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds fifty (50%) percent of the market value of the structure before the start of construction of the improvement. This term includes structures which have incurred substantial damage, regardless of the actual repair work performed. The term does not, however, include either:

- a. Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the Codes Enforcement Officer and which are the minimum necessary to assure safe living conditions; or,
- b. Any alteration of a Historic Structure, provided that the alteration will not preclude the structure's continued designation as a historic structure, and a variance is obtained from the Board of Appeals.

Variance - a grant of relief by the Board of Appeals from the terms of a floodplain management regulation.

Violation - the failure of a structure or development to comply with a community's floodplain management regulations.

ARTICLE XV - ABROGATION

This Ordinance repeals and replaces any municipal ordinance previously enacted to comply with the National Flood Insurance Act of 1968 (P.L. 90-488, as amended).

ARTICLE XVI - DISCLAIMER OF LIABILITY

The degree of flood protection required by this Ordinance is considered reasonable but does not imply total flood protection.

ARTICLE XVII – DATE OF APPLICABILITY

Notwithstanding 1 M.R.S.A. § 302, the date of applicability of this Ordinance, adopted and made effective by a vote of the Town Council on June 18, 2024, shall be June 20, 2024.