WHITETAIL DRIVE SUBDIVISION 1473 U.S. ROUTE ONE, FREEPORT, MAINE SHEET INDEX

PREPARED BY:

CIVIL ENGINEER/SURVEYOR: TERRADYN CONSULTANTS, LLC 41 CAMPUS DR. SUITE 101 NEW GLOUCESTER, MAINE 04260 (207) 926-5111

WETLANDS SURVEY: BASSWOOD ENVIRONMENTAL 93 MILL ROAD CAPE ELIZABETH, MAINE 04107 (207) 518-8442

SITE EVALUATOR: MARK CENCI, GEOLOGIC, INC. 93 MILL ROAD NORTH YARMOUTH, MAINE 04097 (207) 329-3524

APPLICANT/OWNER:

WILLIAM DAVENPORT & TODD HARRISON 321 AUBURN POWNAL ROAD DURHAM, MAINE 04222

PROJECT PARCEL SITE

TOWN OF FREEPORT TAX ASSESSOR'S MAP & LOT NUMBERS <u>MAP</u> 18

<u>LOT</u> 17

APPROVAL: TOWN OF FREEPORT
PROJECT REVIEW BOARD
DATE
CHAIRPERSON



LOCATION MAP SCALE: 1" = 200'

C-1.0	COVER SHEET & LOCATION MAP
S-1.0	BOUNDARY SURVEY
C-2.0	SUBDIVISION PLAN
C-3.0	SITE AND UTILITY PLAN
C-4.0	GRADING AND DRAINAGE PLAN
C-5.0	PROFILE: WHITETAIL DRIVE
C-6.0	EROSION CONTROL DETAILS
C-6.1	SITE DETAILS & NOTES
C-6.2	STORMWATER DETAILS

LEGEND					
	EXISTING PROPERTY LINE				
	PROPOSED SETBACK LINE				
	EXISTING SETBACK LINE				
- · _ · _ · _ · _ · _ · _					
	PROPOSED EASEMENT ROAD CENTERLINE				
124	EXISTING MINOR CONTOUR				
124	EXISTING MAJOR CONTOUR				
124	PROPOSED CONTOUR	F	+	$\left \right $	
SD	EXISTING STORMDRAIN				
ONE	& TELEPHONE				
OHE	PROPOSED OVERHEAD ELECTRIC	F	+	$\left \right $	
	& TELEPHONE				
UGE	EXISTING UNDERGROUND		301	260	
			ц Е	14	
0 <u>0</u> E 	ELECTRIC & TELEPHONE			S, Z	
	EXISTING EDGE OF PAVEMENT			STE	
	PROPOSED EDGE OF PAVEMENT		ظ v این	й С С	
	EXISTING EDGE OF GRAVEL		KES!		ш
			DDF		NOL
	EAISTING TREE LINE PROPOSED TREETINE	Ļ		Ξ	Ъ.
0	CHAIN LINK FENCE				
o	PROPOSED FENCE				
SF	PROPOSED GUARDRAIL SILT FENCE				
	PROPOSED TRANSFORMER		3		
*	PROPOSED LIGHT POLE				
-0-	EXISTING UTILITY POLE				
-0-	PROPOSED UTILITY POLE				
	PROPOSED CATCH BASIN	Ļ			
+ 30.20	EAISTING SPOT GRADE PROPOSED SPOT GRADE		NC		RM
×	EXISTING SIGN	F			
	PROPOSED SIGN				
TP-A	TEST PIT				
	EXISTING BUILDING				
	PROPOSED BUILDING				
<u>, 1117 - 1117</u>	WETLAND AREA				
<u>\\!`</u> <u>\\!`</u>	WETLAND DISTURBANCE		Z	2	
	PROPOSED PAVEMENT		C)	
	RIPRAP) >	
	BUFFER			, 户 一	
	EXPOSED LEDGE		a a	MAIN	
	NON-DISTURBANCE STREAM SETBACK AREA			LEEPORT,	
				ONE, FR	

JC SF	PROJECT:			ADDRESS.			DA		
;al)B N Hee	MHITETAIL DRIVE SUBDIVISION	NO		41 CAMPUS DRIVE. SUITE 301			ATE		
. <u>⊢:</u> NO: T:	1 1 1473 U.S. ROUTE ONE, FREEPORT, MAINE	PE T F		NEW GLOUCESTER, ME 04260					
				(207) 926-5111			U C/CE //// ////	ENN	
	COVER SHEEL / LOCATION MAR				4 09-26-2	23 PRELIMINARY SUBMISSION TO TOWN OF FREEPORT	AL) F) F 142	
С	0 CLIENT:			WEB SITE:	3 06-27-2	23 SUBMITTED SITE INVENTORY & ANALYSIS CONCEPTUAL PLANS		111, MA '''''' 8. Fl 52	
1" ;-(WILLIAM DAVENPORT & TODD HARRISON		ASULIAN IS, LLC	www.terradynconsultants.com	2 03-21-2	23 REVISED CLIENT NAME	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
= 2 22 0.		G	Civil Engineering Land S	urveving I Geomatics	1 01-27-2	23 PLANTING PLAN INFORMATION ADDED IN RESPONSE TO DEP COMMENTS	26-2	ER & VII	
-57 0	E DURHAM, MAINE 04222	Stormv	/ater Design Land Plannir	ng Environmental Permitting	NO. DAT	REVISIONS	2 2023		
C:\OD\Terradvn	Consultants/Project Folders - Documents/2022 Jobs/22-57 Boute One Subdivision Freebort/CAD/Permittina/22-57 C	dwa							7



Summers pute One of 17-A Pg 136	Nu do to Scale Beasant Hill Rd	DATE: PLS:	JIMMY COURBE No. PLS: No. PLS: No SUR 11/14/	MA INC. C. 201 2532 0.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1	DATE PLS
VP1-11 VP1-12 VP1-13	Existing Record Property Line/R.O.W. Abutter Line/R.O.W. Abutter Line/R.O.W. Building Setback Line 250' setback Line 250' setback from Vernal Pool Building Building Overnang Edge of Pavement Edge of Pavement Edge of Gravel Image: Setback Line Softer Elevation Image: Setback Line Storm Drain Image: Setback Line Exposed Ledge Image: Setback Line Image: Setback Line Image: Setback Line Exposed Ledge Image: Setback Line Image: Setback Line Image: Setback Line Image: Setback Line Image: Setback Line Image: Setback Line Image: Setback Line Image: Setback Lin				14/2022 ISSUED DRAFT FOR CLIENT REVIEW. DATE REVISIONS
	General Notes: 1. The purpose of this plan is to depict the results of an Existing Conditions and Topographic Survey of a portion of the subject parcel. 2. All Book and Page numbers refer to the Cumberland County Registry of Deeds, unless otherwise noted. 3. The record owner of the subject parcel is William P. Davenport & Todd Harrison by a deed dated May 29, 2013 and recorded in Book 31208, Page 33. 4. The subject parcel is shown on the Town of Freeport Tax Map 18 as Lot 17 and is located in the Medium Density A District (MDA). 5. Space and bulk standards for the MDA District as of the date of this plan are as follows: Min. Lot Size: 50,000 s.f. Min. Frontage: 200 ft. Min. FrontSetback: 50 ft. Min. Rear Setback: 50 ft. Min. Rear Setback: 50 ft. Max. Building Height: 35 ft. 6. Total area of the subject parcel shown hereon is 8.2 acres. 7. Boundary information is based solely on Plan Ref 8.A. Topographic information shown hereon is based on an on the ground survey conducted by Terradyn Consultants. LLC in November of 2022. 8. Plan References: ^Plan of Land on U.S. Route One, Freeport, Maine, for William P. Davenport & Todd Harrison" dated May 2021 by Wayne T. Wood & Co. and being previously unrecorded.	ADDRESS: 41 CAMPUS DRIVE, SUITE 301 NEW GLOUCESTER, ME 04260	FEDDADY (207) 926-5111	CONSULTANTS, LLC Www.terradynconsultants.com	Civil Engineering Land Surveying Geomatics 1 Stormwater Design Land Planning Environmental Permitting NO. D
	 Plan orientation is Grid North, Maine State Plane Coordinate System, West Zone 1802-NAD83. Elevations depicted hereon are NAVD88, based on dual-frequency GPS observations. NAVD88-Geoid18 (2010.000) error (95% confidence interval) in meters = 0.036 The subject parcel is located within Zone C., areas of minimal flood hazard, as delineated on the Flood Insurance Rate Map for the Town of Freeport, Cumberland County, Community-Panel Number 230046 0010 B. having an Effective Date of January 17, 1985. A wetland delineation was performed on this project site by Basswood Environmental on October 11, 2022 and the Vernal Pool delineation in April & May of 2022. This wetlands delineation conforms to the standards and mothods outlined in the 1987 Wetland Delineation Manual and Northeast Regional Supplement authored and published by the U.S. Army Corps of Engineers. All Wetland flags were located using Global Positioning System (GPS) technology capable of decimeter accuracy. The depth, size, location, existence or nonexistence of underground utilities and/or structures were not investigated as part of this survey. Utilities depicted hereon may not necessarily represent all existing utilities. Owners, contractors, and/or designers need to contact Dig-Safe Systems, inc. (call 811) and field verify existing utilities prior to digging or breaking ground. 	PROJECT: NOT FO NOT FO	SHEET TITLE: EXISTING CONDITIONS PLAN		NOIT NOIT



GENERAL	NOTES:

1. THE RECORD OWNER OF THE PARCEL IS NOW OR FORMERLY WILLIAM P. DAVENPORT & TODD HARRISON BY DEED RECORDED IN THE CUMBERLAND COUNTY REGISTRY OF DEEDS IN BOOK 31208, PAGE 33.

2. THE PROPERTY IS SHOWN AS LOT 17 ON THE TOWN OF FREEPORT TAX MAP 18 AND IS LOCATED IN THE MEDIUM DENSITY A DISTRICT (MDA).

MEDIUM DENSITY A DISTRICT - OPEN SPACE SUBDIVISION 2+ FAMILY MIN. LOT SIZE:10,000 SF/UNIT

MIN. STREET FRONT	AGE:		-		.75 FT.	
MIN. FRONT YARD:					.30 FT.	
MIN. SIDE YARD: .			-		.10 FT.	
MIN. REAR YARD:					.25 FT.	
MAX. BUILDING HEIGI	HT:				.35 FT.	
MAX. IMPERVIOUS SU	JFACE ⁻	TO LO	T ARE	A:	.30 %	
					001	

5. BOUNDARY INFORMATION IS BASED SOLELY ON "PLAN OF LAND ON U.S. ROUTE ONE, FREEPORT, MAINE FOR WILLIAM P. DAVENPORT & TODD HARRISON" DATED MAY 2021 BY WAYNE T. WOOD &. TOPOGRAPHIC INFORMATION SHOWN HEREON IS BASED UPON AN ON THE GROUND SURVEY CONDUCTED BY TERRADYN CONSULTANTS, LLC IN NOVEMBER OF

6. WETLAND & VERNAL POOL INFORMATION SHOWN HEREON IS BASED UPON WETLAND DELINEATION & VERNAL POOL DELINEATION PERFORMED BY BASSWOOD ENVIRONMENTAL IN APRIL, MAY, JULY & OCTOBER OF 2022.

7. THE SUBJECT PARCEL IS LOCATED WITHIN ZONE C, AREAS OF MINIMAL FLOOD HAZARD, AS DELINEATED ON THE FLOOD INSURANCE RATE MAP FOR THE TOWN OF FREEPORT, CUMBERLAND COUNTY, COMMUNITY PANEL #230046-0010B, HAVING AN EFFECTIVE DATE OF JANUARY 17, 1985.

CENTERLINE CURVE TABLE

CURVE	LENGTH	RADIUS	CRD. BEARING	CRD. DIST.
C1	97.01'	150.00'	S 66°10'36" E	95.33'
C2	158.86'	150.00'	S 17°18'29" E	151.54'

PROPERTY CURVE TABLE

CURVE	LENGTH	RADIUS	CRD. BEARING	CRD. DIST
C3	26.15'	25.00'	N 65°19'57" E	24.97'
C4	80.84'	125.00'	S 66°10'36" E	79.44'
C5	132.38'	125.00'	S 17°18'29" E	126.28'
C6	185.34'	175.00'	S 17°18'29" E	176.80'
C7	39.27'	25.00'	N 31°58'04" W	35.36'
C8	39.27'	25.00'	N 58°01'56" E	35.36'

PROPERTY LINE TABLE

LINE	DIRECTION	DISTANCE	
L1	S 42°21'06" W	4.10'	
L2	S 77°09'07" E	28.08'	
L3	S 77°09'07" E	50.00'	
L4	S 13°01'56" W	50.00'	

STATE OF MAINE

PLAN BOOK _____

ATTEST



TE OF MA



A HAB	DATE: 09-26-2023
	PRELIMINARY SUBMISSION TO TOWN OF FREEPORT SUBMITTED SITE INVENTORY & ANALYSIS CONCEPTUAL PLANS REVISED CLIENT NAME PLANTING PLAN INFORMATION ADDED IN RESPONSE TO DEP COMMENTS REVISIONS
1	09-26-2023 09-26-2023 06-27-2023 03-21-2023 03-21-2023 01-27-2023
	S.dwd * S.dwd * S.dwd * S.dwd * S.dwd * S.dwd * S.dwd
GRAPHIC SCALE (N FEET) INCH = 40 FT.	PROJECT: PROJECT: WHITETAIL DRIVE SUBDIVISION 1473 U.S. ROUTE ONE, FREEPORT, MAINE 1575 D. HERT 1500 T.S. ROUTE ONE, FREEPORT, MAINE 1500 T.S. ROUTE ONE, FREEPORT, MAINE 1500 T.S. ROUTE ONE SUBJOINE



	ADRIENNE R. FINE No. 14252	
	E STUDALE RANGENSED	
E -	DATE: 09-26-	2023
30 PH		
	PORT CEPTUAL	
	DF FREEF	
	ADDFD ADDFD	
	SION TO NTORY 8	
	SUBMIS ITE INVEI INT NAME	
	MINARY EED CLIEI STING PLA	SNOI
	PRELI SUBM REVIS	REVIS
	26-2023 27-2023 27-2023	DATE
	01-2	
	04260 Som 04260	tting
	STER, ME onsultants.c	natics ital Permi
	AMPUS DF AMPUS DF GLOUCE3 GLOUCE3 SLITE: SSITE: .terradyncc	ng Geor Nironmen
	ADD NEW (207) WWW	a surveyi nning En
		ring Lan Land Plai
		Enginee Design
OPEN SPACE 2		ormwater
	PERMIT DRAWING	ی NON B
		22-57 G.dw
	NOS NOS	\Permitting\
علاد	ARRI	eeport\CAD
علاد	SION DD H	odivision, Fr
<u>vulu</u>	GE P & TOI	ute One Sut
	SUB AINA DRT a	is∖22-57 Roi
	ENP((UAU ts/2022 Job
	AIL DI E ONE, F DAV	UVNAL R E 04222
	CT: TET/ JDINC S. ROUT JDINC	AM, MAIN Ject Folders
	PROJE SHEET CLIENT CLIENT	DURH ² Sultants/Pro
GRAPHIC SCALE 40 0 20 40 40 0 20 40	DATE: 01-09-2 80 SCALE: 1" JOB NO: 22	2023 löo =40' loo 2-57 lõo Loopeli
(IN FEET) 1 INCH = 40 FT.	SHEET: C-4	



JC SF	ୁ ଜୁ PROJECT:			ADDRESS:			DA
B N HEE	I P A WHITETAIL DRIVE SUBDIVISION	NO.		41 CAMPUS DRIVE. SUITE 301			
NO: T:	I III 1473 U.S. ROUTE ONE, FREEPORT, MAINE	PE T F		NEW GLOUCESTER, ME 04260			
				(207) 926-5111			
					4 09-26-2023	PRELIMINARY SUBMISSION TO TOWN OF FREEPORT	
С	B CLIENT:			WEB SITE:	3 06-27-2023	SUBMITTED SITE INVENTORY & ANALYSIS CONCEPTUAL PLANS	2. FI 52
;-,	I I I I I I I I I I I I I I I I I I I			www.terradynconsultants.com	2 03-21-2023		
^{22.}		G	Civil Engineering Land Sur	veving Geomatics	1 01-27-2023	PLANTING PLAN INFORMATION ADDED IN RESPONSE TO DEP COMMENTS	6-2
-57 0	Z Z DURHAM, MAINE 04222	Stormw ^a	ater Design Land Planning	Environmental Permitting	IO. DATE	REVISIONS	2023
C:\OD\Terrad	1yn Consultants/Project Folders - Documents/2022 Jobs/22-57 Route One Subdivision, Freeport/CAD/Permitting/22-57 G.	lwg					-

EROSION AND SEDIMENT CONTROL PLAN

Pre-Construction Phase

materials shall take measures to prevent unreasonable erosion of soil or sediment beyond the project site or into a protected natural resource as defined in 38 mrsa § 480-b. Erosion control measures must be in place before the activity begins. Measures must remain in place and functional until the site is permanently stabilized. Adequate and timely temporary and permanent stabilization measures must be taken. The site must be maintained to prevent unreasonable erosion and sedimentation. Minimize disturbed areas and protect natural downgradient buffer areas to the extent practicable.

BMP Construction Phase

A. Sediment barriers. Prior to the beginning of any construction, properly install sediment barriers at the edge of any downgradient disturbed area and adjacent to any drainage channels within the proposed disturbed area. Maintain the sediment barriers until the disturbed area is permanently stabilized.

B. Construction entrance: Prior to any clearing or grubbing, a construction entrance shall be constructed at the intersection with the proposed access drive and the existing roadway to avoid tracking of mud, dust and debris from the site.

C. Riprap: Since riprap is used where erosion potential is high, construction must be sequenced so that the riprap is put in place with the minimum delay. Disturbance of areas where riprap is to be placed should be undertaken only when final preparation and placement of the riprap can follow immediately behind the initial disturbance. Where riprap is used for outlet protection, the riprap should be placed before or in conjunction with the construction of the pipe or channel so that it is in place C. Apply hay mulch at twice the standard rate (150 lbs. Per 1,000 sf). The mulch must be thick enough such that the when the pipe or channel begins to operate. Maintain temporary riprap, such as temporary check dams until the disturbed area is permanently stabilized.

D. Temporary stabilization. Stabilize with temporary seeding, mulch, or other non-erodable cover any exposed soils that will remain unworked for more than 14 days except, stabilize areas within 100 feet of a wetland or waterbody within 7 days or prior to a predicted storm event, whichever comes first. If hay or straw mulch is used, the application rate must be 2 bales (70-90 pounds) per 1000 sf or 1.5 to 2 tons (90-100 bales) per acre to cover 75 to 90% of the ground surface. Hay mulch must be kept moist or anchored to prevent wind blowing. An erosion control blanket or mat shall be used at the base of grassed waterways, steep slopes (15% or greater) and on any disturbed soil within 100 feet of lakes, streams and wetlands. Grading shall be planned so as to minimize the length of time between initial soil exposure and final grading. On large projects G. Winter excavation and earthwork shall be completed so that no more than 1 acre of the site is without stabilization at this should be accomplished by phasing the operation and completing the first phase up to final grading and seeding before any one time. starting the second phase, and so on.

E. Vegetated waterway. Upon final grading, the disturbed areas shall be immediately seeded to permanent vegetation and mulched and will not be used as outlets until a dense, vigorous vegetative cover has been obtained. Once soil is exposed for I. Temporary mulch must be applied within 7 days of soil exposure or prior to any storm event, but after every workday waterway construction, it should be immediately shaped, graded and stabilized. Vegetated waterways need to be stabilized early during the growing season (prior to september 15). If final seeding of waterways is delayed past september 15. emergency provisions such as sod or riprap may be required to stabilize the channel. Waterways should be fully stabilized prior to directing runoff to them.

Permanent stabilization defined

A. Seeded areas. For seeded areas, permanent stabilization means an 90% cover of the disturbed area with mature, healthy plants with no evidence of washing or rilling of the topsoil.

B. Sodded areas. For sodded areas, permanent stabilization means the complete binding of the sod roots into the underlying M. All vegetated ditch lines that have not been stabilized by november 1, or will be worked during the winter construction soil with no slumping of the sod or die-off.

C. Permanent mulch. For mulched areas, permanent mulching means total coverage of the exposed area with an approved mulch material. Erosion control mix may be used as mulch for permanent stabilization according to the approved application rates and limitations.

D. Riprap. For areas stabilized with riprap, permanent stabilization means that slopes stabilized with riprap have an appropriate backing of a well-graded gravel or approved geotextile to prevent soil movement from behind the riprap. Stone must be sized appropriately. It is recommended that angular stone be used.

E. Agricultural use. For construction projects on land used for agricultural purposes (e.G., pipelines across crop land), permanent stabilization may be accomplished by returning the disturbed land to agricultural use.

F. Paved areas. For paved areas, permanent stabilization means the placement of the compacted gravel subbase is completed.

G. Ditches, channels, and swales. For open channels, permanent stabilization means the channel is stabilized with mature vegetation at least three inches in height, with well-graded riprap, or with another non-erosive lining capable of withstanding the anticipated flow velocities and flow depths without reliance on check dams to slow flow. There must be no evidence of slumping of the lining, undercutting of the banks, or down-cutting of the channel.

General Construction Phase

The following erosion control measures shall be followed by the contractor throughout construction of this project:

A. All topsoil shall be collected, stockpiled, seeded with rye at 3 pounds/1,000 sf and mulched, and reused as required. Silt fencing shall be placed down gradient from the stockpiled loam. Stockpile to be located by designation of the owner and inspecting engineer.

B. The inspecting engineer at his/her discretion, may require additional erosion control measures and/or supplemental vegetative provisions to maintain stability of earthworks and finish graded areas. The contractor shall be responsible for providing and installing any supplemental measures as directed by the inspecting engineer. Failure to comply with the engineer's directions will result in discontinuation of construction activities.

C. Erosion control mesh shall be applied in accordance with the plans over all finish seeded areas as specified on the design plans.

D. All graded or disturbed areas including slopes shall be protected during clearing and construction in accordance with the approved erosion and sediment control plan until they are adequately stabilized.

E. All erosion, and sediment control practices and measures shall be constructed, applied and maintained in accordance with the approved erosion and sediment control plan.

F. Areas to be filled shall be cleared, grubbed and stripped of topsoil to remove trees, vegetation, roots or other objectionable materials.

G. Areas shall be scarified to a minimum depth of 3 inches prior to placement of topsoil.

H. All fills shall be compacted as required to reduce erosion, slippage, settlement, subsidence or other related problems. Fill intended to support buildings, structures and conduits, etc., shall be compacted in accordance with local requirements or codes

I. All fills shall be placed and compacted in layers not to exceed 8 inches in thickness.

J. Except for approved landfills or non-structural fills, fill material shall be free of brush, rubbish, rocks, logs, stumps, building debris and other objectionable materials that would interfere with or prevent construction of satisfactory lifts.

K. Frozen material or soft, mucky or highly compressible materials shall not be incorporated into fill slopes or structural fills.

L. Fill shall not be placed on a frozen foundation.

M. Seeps or springs encountered during construction shall be handled appropriately.

N. All graded areas shall be permanently stabilized immediately following finished grading.

O. Remove any temporary control measures, such as silt fence, within 30 days after permanent stabilization is attained. Remove any accumulated sediments and stabilize.

Permanent vegetation

Permanent vegetative cover should be established on disturbed areas where permanent, long lived vegetative cover is needed to stabilize the soil, to reduce damages from sediment and runoff, and to enhance the environment.

Seedbed preparation

A. Grade as feasible to permit the use of conventional equipment for seedbed preparation, seeding, mulch application and anchoring, and maintenance.

B. Apply limestone and fertilizer according to soil tests such as those offered by the university of maine soil testing laboratory. Soil sample mailers are available from the local cooperative extension service office. If soil testing is not feasible on small or variable sites, or where timing is critical, fertilizer may be applied at the rate of 800 pounds per acre or 18.4 pounds per 1,000 square feet using 10-20-20 (n-p2o5-k2o) or equivalent. Apply ground limestone (equivalent to 50% calcium plus magnesium oxide) at

a rate of 3 tons per acre (138 lb. Per 1,000 sq. Ft).

C. Work lime and fertilizer into the soil as nearly as practical to a depth of 4 inches with a disc, spring tooth harrow or other suitable equipment. The final harrowing operation should be on the general contour. Continue tillage until a reasonably uniform, fine seedbed is prepared. All but clay or silty soils and coarse sands should be rolled to firm the seedbed wherever feasible.D. Remove from the surface all stones 2 inches or larger in any dimension. Remove all other debris, such as wire, cable, tree roots, concrete, clods, lumps or other unsuitable material.

E. Inspect seedbed just before seeding. If traffic has left the soil compacted; the area must be tilled and firmed as above.

F. Permanent seeding should be made 45 days prior to the first killing frost or as a dormant seeding with mulch after the first killing frost and before snowfall. When crown vetch is seeded in later summer, at least 35% of the seed should be hard seed (unscarified). If seeding cannot be done within the seeding dates, mulch according to the temporary mulching bmp and overwinter stabilization and construction to protect the site and delay seeding until the next recommended seeding period.

annual ryegrass and 5% white dutch clover.

should be seeded at the beginning of the growing season.

additional stabilization measures.

in areas within 100 feet from a protected natural resource.

Maintenance and inspection phase

until areas are permanently stabilized.



NOT TO SCALE

USED TO TRAP SEDIMENT.

NOT TO SCALE





CONSTRUCTION NOTES TE OF MA 1. ALL WORK SHALL CONFORM TO THE APPLICABLE CODES AND ORDINANCES. ADRIENNE R. FINE 2. CONTRACTOR SHALL VISIT THE SITE AND FAMILIARIZE HIM OR HERSELF WITH ALL CONDITIONS AFFECTING No. 14252 THE PROPOSED WORK AND SHALL MAKE PROVISIONS AS TO THE COST THEREOF. CONTRACTOR SHALL BE Alme Time RESPONSIBLE FOR FAMILIARIZING HIM OR HERSELF WITH ALL CONTRACT DOCUMENTS, FIELD CONDITIONS AND DIMENSIONS AND CONFIRMING THAT THE WORK MAY BE ACCOMPLISHED AS SHOWN PRIOR TO ONAL PROCEEDING WITH CONSTRUCTION. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO THE COMMENCEMENT OF WORK. DATE: 09-26-2023 3. CONTRACTOR SHALL NOTIFY ENGINEER OF ALL PRODUCTS OR ITEMS NOTED AS "EXISTING" WHICH ARE NOT FOUND IN THE FIELD. 4. INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND OWNER'S REQUIREMENTS UNLESS SPECIFICALLY OTHERWISE INDICATED OR WHERE LOCAL CODES OR REGULATIONS TAKE PRECEDENCE. 5. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS IN THE FIELD PRIOR TO FABRICATION AND ERECTION OF ANY MATERIAL. ANY UNUSUAL CONDITIONS SHALL BE REPORTED TO THE ATTENTION OF THE ENGINEER. 6. CONTRACTOR SHALL CLEAN AND REMOVE DEBRIS AND SEDIMENT DEPOSITED ON PUBLIC STREETS, SIDEWALKS, ADJACENT AREAS, OR OTHER PUBLIC WAYS DUE TO CONSTRUCTION. 7. CONTRACTOR SHALL INCORPORATE PROVISIONS AS NECESSARY IN CONSTRUCTION TO PROTECT EXISTING STRUCTURES, PHYSICAL FEATURES, AND MAINTAIN SITE STABILITY DURING CONSTRUCTION. CONTRACTOR SHALL RESTORE ALL AREAS TO ORIGINAL CONDITION AND AS DIRECTED BY DESIGN DRAWINGS. 8. SITE CONTRACTOR SHALL OBTAIN ALL REQUIRED PERMITS PRIOR TO CONSTRUCTION. 9. ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSTALLED IN ACCORDANCE WITH "MAINE EROSION AND SEDIMENTATION CONTROL HANDBOOK FOR CONSTRUCTION: BEST MANAGEMENT PRACTICES" PUBLISHED BY THE CUMBERLAND COUNTY SOIL AND WATER CONSERVATION DISTRICT AND MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION. MARCH 2016 OR LATEST EDITION. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO POSSESS A COPY OF THE EROSION CONTROL PLAN AT ALL TIMES 10. THE CONTRACTOR IS HEREBY CAUTIONED THAT ALL SITE FEATURES SHOWN HEREON ARE BASED ON FIELD OBSERVATIONS BY THE SURVEYOR AND BY INFORMATION PROVIDED BY UTILITY COMPANIES. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE. THE CONTRACTOR SHALL CONTACT DIG SAFE (1-888-DIGSAFE) AT LEAST THREE (3) BUT NOT MORE THAN THIRTY (30) DAYS PRIOR TO COMMENCEMENT OF EXCAVATION OR DEMOLITION TO VERIFY HORIZONTAL AND VERTICAL LOCATION OF ALI UTILITIES. 11. CONTRACTOR SHALL BE AWARE THAT DIG SAFE ONLY NOTIFIES ITS "MEMBER" UTILITIES ABOUT THE DIG. WHEN NOTIFIED, DIG SAFE WILL ADVISE CONTRACTOR OF MEMBER UTILITIES IN THE AREA. CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING AND CONTACTING NON-MEMBER UTILITIES DIRECTLY. NON-MEMBER UTILITIES MAY INCLUDE TOWN OR CITY WATER AND SEWER DISTRICTS AND SMALL LOCAL UTILITIES, AS WELL AS USG PUBLIC WORKS SYSTEMS. 12. CONTRACTORS SHALL BE RESPONSIBLE FOR COMPLIANCE WITH THE REQUIREMENTS OF 23 MRSA 3360-A. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE WITH THE APPROPRIATE UTILITIES TO OBTAIN AUTHORIZATION PRIOR TO RELOCATION OF ANY EXISTING UTILITIES WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THESE PLANS. IF A UTILITY CONFLICT ARISES, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE OWNER, THE MUNICIPALITY AND APPROPRIATE UTILITY COMPANY PRIOR TO PROCEEDING WITH ANY RELOCATION. 13. ALL PAVEMENT MARKINGS AND DIRECTIONAL SIGNAGE SHOWN ON THE PLAN SHALL CONFORM TO THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) STANDARDS. 14. ALL PAVEMENT JOINTS SHALL BE SAWCUT PRIOR TO PAVING TO PROVIDE A DURABLE AND UNIFORM JOINT. 15. NO HOLES. TRENCHES OR STRUCTURES SHALL BE LEFT OPEN OVERNIGHT IN ANY EXCAVATION ACCESSIBLE TO THE PUBLIC OR IN PUBLIC RIGHTS-OF-WAY. 16. ALL WORK WITHIN THE PUBLIC RIGHT-OF-WAY SHALL REQUIRE A M.D.O.T. PERMIT AS WELL AS PERMITS FROM THE TOWN AS APPLICABLE 17. THE PROPOSED LIMITS OF CLEARING SHOWN HEREON ARE APPROXIMATE BASED UPON THE PROPOSED LIMITS OF SITE GRADING. THE APPLICANT RESERVES THE RIGHT TO PERFORM NORMAL FOREST MANAGEMENT ACTIVITIES OUTSIDE OF THE CLEARING LIMIT AS SHOWN. TREE REMOVAL OUTSIDE OF THE LIMITS OF CLEARING MAY BE NECESSARY TO REMOVE DEAD OR DYING TREES OR TREE LIMBS. THIS PHONE: (207) 926 REMOVAL IS DUE TO POTENTIAL SAFETY HAZARDS AND TO PROMOTE PROPER FOREST GROWTH. - <u>4</u> 1 1 18. IMMEDIATELY UPON COMPLETION OF CUTS/FILLS, THE CONTRACTOR SHALL STABILIZE DISTURBED AREAS IN ACCORDANCE WITH EROSION CONTROL NOTES AND AS SPECIFIED ON PLANS. 19. THE CONTRACTOR SHALL BE FULLY AND SOLELY RESPONSIBLE FOR THE REMOVAL, REPLACEMENT AND RECTIFICATION OF ALL DAMAGED AND DEFECTIVE MATERIAL AND WORKMANSHIP IN CONNECTION WITH THE CONTRACT WORK. THE CONTRACTOR SHALL REPLACE OR REPAIR AS DIRECTED BY THE OWNER ALL SUCH DAMAGED OR DEFECTIVE MATERIALS WHICH APPEAR WITHIN A PERIOD OF ONE YEAR FROM THE DATE OF RRA SUBSTANTIAL COMPLETION. 20. ALL WORK PERFORMED BY THE GENERAL CONTRACTOR AND/OR TRADE SUBCONTRACTOR SHALL CONFORM TO THE REQUIREMENTS OF LOCAL, STATE OR FEDERAL LAWS, AS WELL AS ANY OTHER GOVERNING REQUIREMENTS, WHETHER OR NOT SPECIFIED ON THE DRAWINGS. 21. WHERE THE TERMS "APPROVED EQUAL", "OTHER APPROVED", "EQUAL TO", "ACCEPTABLE" OR OTHER GENERAL QUALIFYING TERMS ARE USED IN THESE NOTES, IT SHALL BE UNDERSTOOD THAT REFERENCE IS PERMIT DRAWING MADE TO THE RULING AND JUDGMENT OF TERRADYN CONSULTANTS, LLC. NOT FOR CONSTRUCTION 22. THE GENERAL CONTRACTOR SHALL PROVIDE ALL NECESSARY PROTECTION FOR THE WORK UNTIL TURNED OVER TO THE OWNER. NO 23. THE GENERAL CONTRACTOR SHALL MAINTAIN A CURRENT AND COMPLETE SET OF CONSTRUCTION DRAWINGS ON SITE DURING ALL PHASES OF CONSTRUCTION FOR USE OF ALL TRADES. HARRIS 24. THE CONTRACTOR SHALL TAKE FULL RESPONSIBILITY FOR ANY CHANGES AND DEVIATION OF APPROVED PLANS NOT AUTHORIZED BY THE ARCHITECT/ENGINEER AND/OR CLIENT/OWNER. 25. DETAILS ARE INTENDED TO SHOW END RESULT OF DESIGN. ANY MODIFICATION TO SUIT FIELD DIMENSION Z AND CONDITION SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW AND APPROVAL PRIOR TO ANY WORK. \square 26. BEFORE THE FINAL ACCEPTANCE OF THE PROJECT, THE CONTRACTOR SHALL REMOVE ALL EQUIPMENT \square S AND MATERIALS, REPAIR OR REPLACE PRIVATE OR PUBLIC PROPERTY WHICH MAY HAVE BEEN DAMAGED OR Ο DESTROYED DURING CONSTRUCTION, CLEAN THE AREAS WITHIN AND ADJACENT TO THE PROJECT WHICH HAVE BEEN OBSTRUCTED BY HIS/HER OPERATIONS, AND LEAVE THE PROJECT AREA NEAT AND SUBDI ^T MANE Š PRESENTABLE. \mathbf{O} 0 DRIVE Ζ **E E N N** ∞ĭ DAV WNAL R AIL AIL PIL -IAM URN PO PROJECI WHIT ⊢Ш CLIEN WIL 321 AU က်က DATE: 01-09-2023

SCALE: JOB NO:

SHEET:

C-6.

22-57



	228.34				
	227				
	225.5				
V.	227				
(SF)	1,227				
E (CF)	2,415				

LOAMY COARSE SAND (12" FILTER LAYER)		LOAMY TOPSOIL (6" TOP LAYER)	
SIEVE #	% PASSING BY WEIGHT	SIEVE #	% PASSING BY WEIGHT
10	85-100	4	75-95
20	70-100	10	60-90
60	15-40	40	38-85
200	8-15	200	20-70